

PROFESSIONAL POWER AMPLIFIER

LECXO

Better Products. Exceptional Quality.

PAM2000X2



➤ 8Ω Stereo Power	2x2000W
➤ 4Ω Stereo Power	2x3400W
➤ 2Ω Stereo Power	2x4000W
➤ 8Ω Bridged Power	6000W
➤ Output Circuitry	Class TD
➤ Frequency Response	20Hz-20KHz+-0.3dB@1W
➤ Signal Noise Ratio(dB)	103dB
➤ THD+N(rated power, 40/KHz)%	<0.08% 8Ω
➤ Damping coefficient	600
➤ Input Impedance	20KΩ balanced/ 10KΩ unbalanced
➤ Input Sensitivity	1V /2V
➤ Protection	Protection from short circuit, open circuit, overheating, overload, DC, supersonic frequency, etc.
➤ Indicators(per Channel)	Protection indicator, signal indicator, work indicator
➤ Power Requirement	AC 220V-240V 50-60Hz
➤ Dimensions	483x545x135mm
➤ Net Weight	35KG
➤ Gross Weight	39KG

No level
power supply

Its power supply
changes depending on
the input signal

It can exceed 10V and can
also exceed 100V
when signal inputs, resulting
in lower power consumption

Class TD has
higher efficiency
than Class H

Its bass is strong and
powerful, which is suitable
for Subwoofer Speaker.

PROFESSIONAL POWER AMPLIFIER

LECXO

Better Products. Exceptional Quality.

PAM400X2



➤ 8Ω Stereo Power	2x400W
➤ 4Ω Stereo Power	2x650W
➤ 2Ω Stereo Power	2x910W
➤ 8Ω Bridged Power	1280W
➤ Output Circuitry	Class AB
➤ Frequency Response	10Hz-20KHz+-0.25dB
➤ Signal Noise Ratio(dB)	101dB
➤ THD+N(rated power, 40/KHz)%	≤0.03% 1KHz
➤ Damping coefficient	≥500
➤ Input Impedance	20KΩ balanced/ 10KΩ unbalanced
➤ Input Sensitivity	0.775V/ 1.0V / 1.4V
➤ Protection	Protection from short circuit, open circuit, overheating, overload, DC, supersonic frequency, etc.
➤ Indicators(per Channel)	Protection indicator, signal indicator, work indicator
➤ Power Requirement	AC 220V-240V 50-60Hz
➤ Dimensions	483x465x90mm
➤ Net Weight	16.5KG
➤ Gross Weight	19KG

PAM400X2 Amplifier is designed for KTV.

Its medium frequency is wide;
when you sing,
you will feel relaxed and enjoy yourself.

The sound is good and smooth

PROFESSIONAL POWER AMPLIFIER

LECxo
Better Products. Exceptional Quality.

PAM1300X2



➤ 8Ω Stereo Power	2x1300W
➤ 4Ω Stereo Power	2x2300W
➤ 2Ω Stereo Power	2x2600W
➤ 8Ω Bridged Power	3800W
➤ Output Circuitry	Class TD
➤ Frequency Response	20Hz-20KHz+0/-0.3dB@1W
➤ Signal Noise Ratio(dB)	103dB
➤ THD+N(rated power, 40/KHz)%	<0.08% 8Ω
➤ Damping coefficient	500
➤ Input Impedance	20KΩ balanced/ 10KΩ unbalanced
➤ Input Sensitivity	1V /2V
➤ Protection	Protection from short circuit, open circuit, overheating, overload, DC, supersonic frequency, etc.
➤ Indicators(per Channel)	Protection indicator, signal indicator, work indicator
➤ Power Requirement	AC 220V-240V 50-60Hz
➤ Dimensions	485x520x90mm
➤ Net Weight	22.4KG
➤ Gross Weight	25.3KG

No level
power supply

Its power supply
changes depending on
the input signal

It can exceed 10V and can
also exceed 100V
when signal inputs, resulting
in lower power consumption

Class TD has
higher efficiency
than Class H

Its bass is strong and
powerful, which is suitable
for Subwoofer Speaker.

PROFESSIONAL POWER AMPLIFIER

LECxo

Better Products. Exceptional Quality.

PAM800X2



➤ 8Ω Stereo Power	2x800W
➤ 4Ω Stereo Power	2x1420W
➤ 2Ω Stereo Power	2x1600W
➤ 8Ω Bridged Power	2300W
➤ Output Circuitry	Class TD
➤ Frequency Response	20Hz-20KHz+0/-0.3dB@1W
➤ Signal Noise Ratio(dB)	103dB
➤ THD+N(rated power, 40/KHz)%	<0.08% 8Ω
➤ Damping coefficient	500
➤ Input Impedance	20KΩ balanced/ 10KΩ unbalanced
➤ Input Sensitivity	1V /2V
➤ Protection	Protection from short circuit, open circuit, overheating, overload, DC, supersonic frequency, etc.
➤ Indicators(per Channel)	Protect indicator, signal indicator, work indicator
➤ Power Requirement	AC 220V-240V 50-60Hz
➤ Dimensions	485x520x90mm
➤ Net Weight	21.4KG
➤ Gross Weight	24.3KG

No level
power supply

Its power supply
changes depending on
the input signal

It can exceed 10V and can
also exceed 100V
when signal inputs, resulting
in lower power consumption

Class TD has
higher efficiency
than Class H

Its bass is strong and
powerful, which is suitable
for Subwoofer Speaker.