

METAL POWER SUPPLY

TECHNICAL PARAMETERS

Common Features



High Quality



Stable Supply



LED Products



CCTV

5V5A



PRODUCT NAME

5V5A

AC Input

100-220V AC 50/60Hz

Persistent Current

5A

Operation Temperature

-10°C~45°C

Product Power

25W

Dimension

110*78*36MM

Product Weight

0.197KG

5V10A



PRODUCT NAME

5V10A

AC Input

100-220V AC 50/60Hz

Persistent Current

10A

Operation Temperature

-10°C~45°C

Door Opening Delay

50W

Dimension

158*97*42MM

Product Weight

0.314KG

METAL POWER SUPPLY

TECHNICAL PARAMETERS

Common Features



High Quality



Stable Supply



LED Products



CCTV

5V20A



PRODUCT NAME

5V20A

AC Input

100-220V AC 50/60Hz

Persistent Current

20A

Operation Temperature

-10°C~45°C

Product Power

100W

Dimension

199*97*42MM

Product Weight

0.46KG

5V30A



PRODUCT NAME

5V30A

AC Input

100-220V AC 50/60Hz

Persistent Current

30A

Operation Temperature

-10°C~45°C

Product Power

150W

Dimension

199*97*42MM

Product Weight

0.526KG

METAL POWER SUPPLY

TECHNICAL PARAMETERS

Common Features



High Quality



Stable Supply



LED Products



CCTV

5V40A



PRODUCT NAME

5V40A

AC Input

100-220V AC 50/60Hz

Persistent Current

40A

Operation Temperature

-10°C~45°C

Product Power

200W

Dimension

199*109*52MM

Product Weight

0.684KG

12V3A



PRODUCT NAME

12V3A

AC Input

100-220V AC 50/60Hz

Persistent Current

3A

Operation Temperature

-10°C~45°C

Product Power

36W

Dimension

110*78*36MM

Product Weight

0.197KG

METAL POWER SUPPLY

TECHNICAL PARAMETERS

Common Features



High Quality



Stable Supply



LED Products



CCTV

12V5A



PRODUCT NAME

12V5A

AC Input

100-220V AC 50/60Hz

Persistent Current

5A

Operation Temperature

-10°C~45°C

Product Power

60W

Dimension

158*97*42MM

Product Weight

0.305KG

12V10A



PRODUCT NAME

12V10A

AC Input

100-220V AC 50/60Hz

Persistent Current

10A

Operation Temperature

-10°C~45°C

Product Power

120W

Dimension

199*97*42MM

Product Weight

0.46KG

METAL POWER SUPPLY

TECHNICAL PARAMETERS

Common Features



High Quality



Stable Supply



LED Products



CCTV

12V15A



PRODUCT NAME

12V15A

AC Input

100-220V AC 50/60Hz

Persistent Current

15A

Operation Temperature

-10°C~45°C

Product Power

180W

Dimension

199*97*42MM

Product Weight

0.496KG

12V20A



PRODUCT NAME

12V20A

AC Input

100-220V AC 50/60Hz

Persistent Current

15A

Operation Temperature

-10°C~45°C

Product Power

240W

Dimension

199*109*50MM

Product Weight

0.626KG

METAL POWER SUPPLY

TECHNICAL PARAMETERS

Common Features



High Quality



Stable Supply



LED Products



CCTV

12V30A



PRODUCT NAME

12V30A

AC Input

100-220V AC 50/60Hz

Persistent Current

30A

Operation Temperature

-10°C~45°C

Product Power

360W

Dimension

215*112*50MM

Product Weight

0.8KG

12V40A



PRODUCT NAME

12V40A

AC Input

100-220V AC 50/60Hz

Persistent Current

40A

Operation Temperature

-10°C~45°C

Door Opening Delay

480W

Dimension

240*125*65MM

Product Weight

1.3KG

METAL POWER SUPPLY

TECHNICAL PARAMETERS

Common Features



High Quality



Stable Supply



LED Products



CCTV

12V50A



PRODUCT NAME

12V50A

AC Input

100-220V AC 50/60Hz

Persistent Current

50A

Operation Temperature

-10°C~45°C

Product Power

600W

Dimension

242*131*68MM

Product Weight

1.64KG

24V2A



PRODUCT NAME

24V2A

AC Input

100-220V AC 50/60Hz

Persistent Current

2A

Operation Temperature

-10°C~45°C

Door Opening Delay

48W

Dimension

110*78*36MM

Product Weight

0.196KG

METAL POWER SUPPLY

TECHNICAL PARAMETERS

Common Features



High Quality



Stable Supply



LED Products



CCTV

24V3A



PRODUCT NAME

24V3A

AC Input

100-220V AC 50/60Hz

Persistent Current

3A

Operation Temperature

-10°C~45°C

Product Power

72W

Dimension

158*97*42MM

Product Weight

0.306KG

24V5A



PRODUCT NAME

24V5A

AC Input

100-220V AC 50/60Hz

Persistent Current

5A

Operation Temperature

-10°C~45°C

Product Power

120W

Dimension

199*97*42MM

Product Weight

0.458KG

METAL POWER SUPPLY

TECHNICAL PARAMETERS

Common Features



High Quality



Stable Supply



LED Products



CCTV

24V10A



PRODUCT NAME

24V10A

AC Input

100-220V AC 50/60Hz

Persistent Current

10A

Operation Temperature

-10°C~45°C

Product Power

240W

Dimension

199*109*50MM

Product Weight

0.634KG

24V15A



PRODUCT NAME

24V15A

AC Input

100-220V AC 50/60Hz

Persistent Current

15A

Operation Temperature

-10°C~45°C

Product Power

360W

Dimension

215*112*50MM

Product Weight

0.786KG

METAL POWER SUPPLY

TECHNICAL PARAMETERS

Common Features



High Quality



Stable Supply



LED Products



CCTV

24V20A



PRODUCT NAME

24V20A

AC Input

100-220V AC 50/60Hz

Persistent Current

20A

Operation Temperature

-10°C~45°C

Product Power

480W

Dimension

240*125*65MM

Product Weight

1.3KG

24V30A



RPRODUCT NAME

24V30A

AC Input

100-220V AC 50/60Hz

Persistent Current

30A

Operation Temperature

-10°C~45°C

Product Power

720W

Dimension

242*131*68MM

Product Weight

1.66KG